

PRO TRADE SERIES



ULTIMATE TRADESMAN TRAILER







BODY SPECIFICATION

- Heavy duty one-piece RHS chassis 100x50x4mm that's fully hot dip galvanized and powder coated
- Precision CNC laser cut and pressed manufacturing processes
- Pressed rear tail gate and sides 400mm high
- 2.5mm aluminum front box, canopy and rear boxes to reduce weight but also keep strength
- Our trailers are fully powder coated
- The rear deck section on the TPHv2 is 1200mm long x 1570mm wide (internal) and also have space between the boxes of 1170mm long x 600mm wide
- The rear section on this model has lockable, gas strutted mesh side walls for extra security
- Front draw bar load support rack that's removable
- Aluminum stone protection plates and foot treads all round
- Automotive seals and gas struts on all doors and draws
- Compression locks on all doors and storage compartments
- Rope tie rails each side and stainless top caps on sides to reduce wear and scratching

RUNNING GEAR

- Independent swing arm suspension with flat top coils and twin shock absorbers
- Dual 12" electric brake hubs with 6 stud Landcruiser stud pattern (139.7 PCD)
- 5 x 15" Primal Alloy rims and quality tyres
- Premium XO series jockey wheel with twin rubber tyre and fully adjustable heights
- 3500kg tow coupling to suit 1% ball with handbrake

STORAGE

Main canopy storage compartment (left side)

- 1200mm wide x 700mm deep to wall
- Floor to shelf 570mm high shelf to

- roof 380mm high shelf is 600mm deep
- Bottom section beside tool boxes is 700mm deep x 500mm wide x 570mm high
- Tool boxes have 4 draws at 120mm high x 540mm wide x 550mm long
- Bottom storage draw is 390mm wide x 870mm long x 260mm high

Main canopy storage compartment (right side)

- 1200mm wide x 1040mm deep to wall
- Floor to shelf 460mm high, shelf to roof 480mm high – shelf is 980mm deep
- Bottom storage draws 390mm wide x 870mm long x 260mm high

Front storage fridge box

- Enclosed front storage box with fridge slide, storage draw and open compartment on opposite side 1800mm long x 700mm wide (both sides of this box has 12 volt Anderson plug power sockets and a fan)
- Fridge slide size area is 850mm long x 550mm wide x 600mm high (to top of draw)
- Draw above fridge area is 830mm long x 530mm wide x 190mm high
- Storage rail system on top of front box for additional items to be carried
- Right side of this box has an area of 700mm wide x 680mm deep x 850mm high (from floor to roof)

Both rear boxes are the same layout

- Bottom platform is 1170mm wide x 550mm deep
- 2x adjustable shelving platforms in the main compartment 1170mm wide x 500mm deep
- Bottom pull out draw is 950mm wide x 550mm deep

Rear trundle draw system

• This rear draw is designed on full ball bearing guides due to its size and strength, size of this draw is 3000mm long x 500mm wide x 140mm high

H-Frame hurdles

- Rear H-Frame hurdle does have a rear roller to assist with ease of loading
- H-Frames are 1770mm wide internal of the horns or 1850mm over all, horns are 100mm high

Water on board

 Twin 40ltr water tanks each side rear of the trailer

ELECTRICAL

- Full LED internal canopy lighting with control management panel
- 2 x 120amp AGM batteries
- 50amp Anderson plug for charging while driving
- Twin 100amp solar panels on roof of rear boxes to MPPT solar controller
- LED tail lights with reverse light, side marker and front clearance lights
- Safety breakaway unit
- The light switch panel and breaker switches are hidden in drawer-like area with swing open door
- Includes Elecbrake Controller

PRO TRADE SERIES **TPHv2**

TARE 1850kg (without added options)

GVM 3500kg

PAYLOAD 1650kg

BALL WEIGHT 180kg (Dry)

OVERALL SIZE 5650mm(L) x 2300mm(W) x 2280mm(H)

\$37,990.00

Pricing may vary depending on final agreed configuration. Specifications are subject to change without notice.

+ GST

FORTRESS TRAILERS LTD

Landscape Lane – Te Awamutu – New Zealand (Located in the STIHL SHOP / Hire Centre complex)

www.fortresstrailers.co.nz

NATIONAL SALES: Matt Hird

EMAIL: matt@fortresstrailers.co.nz / PH: 021 981 932 / 0508 GET ONE 0508 438 663

